

Autodesk®

Fabrication RemoteEntry 2015

Service Pack 4 Enhancement List

Improvements made in Service Pack build 3.03.1164:

General Usability Improvements

- CID 838 - Improved placement of Profile bearer when configured with -ve left or right angled bearer.

Service Pack 3 Enhancement List

Improvements made in Service Pack 3 build 3.03.1162:

Pattern Improvements

- CID 62 - Improved insulation so that it is central on the branch.
- CID 311 - Improved insulation so that it is central on the branch.
- CID 379 - Improved insulation so that it is central on the branches.
- CID 832 - Improved insulation so that it is central on the branches.
- CID 886 - Improved insulation so that it is central on the branch.
- CID 7 - Improved connector size for the C2 end.
- CID 1115 - Improved conical branch to be configured straight.

Service Pack 2 Enhancement List

Improvements made in Service Pack 2 build 3.03.1122:

Pattern Improvements

- Improved usability when removing holes along with seams for straight duct patterns.
- CID 2524 - Stability improvement made when opening job.
- CID 4 - Improved connector straight allowance for extensions.
- CID 4 - Improved Gasket allowance when Double Wall is enabled.
- CID 17 - Improved Gasket allowance when Double Wall is enabled.
- Improved Fabrication items by allowing functions to be used in calculated dims.
- CID 965 - Improved connector positions when using Offset Reducers & geometry when insulated.
- CID 2965 - Improved connector positions when using Offset Reducers & geometry when insulated.
- CID 101 - Improved Imperial dimensions.
- Improved Rectangular Straight Adjusts for Taps.

Service Pack 1 Enhancement List

Improvements made in Service Pack 1 build 3.03.1032:

Pattern Improvements

- CID 535 - Improved Draw Type Options.
- CID 4 - Improved insulation.
- Stability improvement made when removing holes from straight ducts.
- Stability improvement made when loading jobs with dampers.

General Usability Improvements

- Improvement made to allow jobs to be saved.